

# ***Cuvo Pumping Solutions, Inc.***

16535 Hollister St., Ste. C  
Houston TX 77066  
713-460-8828 Direct 713-460-8838 Fax  
www.cuvopumpingsolutions.com

## **Hi-Lo Supreme 10 AWG 2 conductor plus ground jacketed submersible pump cable.**

### **Insulated and jacketed with a premium thermoplastic elastomer (TPE) material.**

#### PACKAGE CABLE

Hi-Lo supreme jacketed type, UL approved cable furnished in pre-cut lengths with water tight Viton plug on one end for direct connection to a Franklin 4" motor. Cable uses stranded copper conductors.


#### APPLICATION

For use with submersible pumps in water wells, cable is UL approved for this application.

Suitable for hot or cold conditions, from -50°C to 105°C, 75°C wet, 60°C in oil.

STPE thermoplastic rubber is inherently resistant to a wide variety of oils, solvents and chemicals.

Section 501-11 of the 1990 National Electric Code, entitled flexible cords, Class 1, Division 1 and 2 (pages 70-442) has been interpreted by inspectors such that a flexible cord is appropriate for use with Electrical Submersible Pump in Class I, Division I, Group D applications, as long as the pump has a means of removal from the "wet-pit" without entering the "wet-pit." This is accomplished by the drop pipe connected to the pump or by the safety cable. The Hi-Lo Supreme STPE lead generally meets the flexible cord requirements as interpreted by these inspectors.



Note: Jacketed cable is trimmed back approximately 2 inches from outer sleeve.

CONSTRUCTION: Jam nut/sleeve - 316 stainless steel, bushing - 4" Viton

CONDUCTORS: **19 STR**

INSULATION: STPE .045" wall nom.

COLOR CODE: Black, Red, Green

OVERALL DIAMETER: 0.258 x 0.667

WEIGHT: 151 lb/1000 ft.