

16535 Hollister Street, Ste. C Houston TX 77066 888.368.8318 Toll Free 713.460.8828. Direct 713.460.8838 Fax

www.cuvopumpintgsolutions.com

TORQUER LOCKING WELL PLUGS



SIZES AVAILABLE

SIZES AVAILABLE	
1/2" Sch.40	3-1/2" Sch.40
3/4" Sch.40	4" Sch.40
3/4" Sch.80	4" Sch.80
1" Sch.40	5" Sch.40
1-1/4" Sch.40	5-1/2" Sch.40
1-1/2" Sch.40	6" Sch.40
2" Sch.40	6-1/2" Sch.40
2" Sch.80	8" Sch.40
2-1/2" Sch.40	
3" Sch.40	

KOBY ENVIRONMENTAL'S SIMPLE-TO-USE RELIABLE LOCKING SYSTEM.

This light-weight locking I.D. plug, truly locks the well. Incorporated is a large wing nut design, for ease of installation and removal. The plug is water tight and florescent orange.

- No metal parts.
- Accepts #1 or #3 type pad locks or Koby Safety Lock
 Out Tags.
- High-tech liquid tight seamless dual rubber gasket.
- Easily disassembled in the field for decon.
- Strong instrument tethering tool. Dual use with anvil tip.
- Manufactured from an engineering grade polymer blend commonly used to replace steel gears in industry, resistant to most chemicals, unaffected by freezing or high temperatures. Smooth acting ergo grip.
- Easy on, easy off wing nut.
- Large, bold, easy-to-read well ID lettering.
- Bright safety coloring.
- Light weight, yet super strong.
- Flush OD design for easy well installation.
- Advanced engineered design will not separate in well.
- Easily convertible for vapor extraction, pressure gauges, vacuum gages and threaded line fittings.
- Domed top prevents liquids from pooling.
- Designed, engineered and manufactured in the U.S.A.