

Pemco Model 104 Locking Monitoring Well Vault

The Locking Monitoring Well Vault allows access to monitoring/observation wells. The vault contains a recessed locking device with a bolted cover which is designed to keep out dirt and debris. The vault features a steel frame, diamond plate steel cover, 16 gauge galvanized steel skirt and carries the H-20 load rating. The locking monitoring well vault is available in square and rectangular Model 104, round Model 104R, and rain tight Model 104WT, which includes a Buna-N gasket and bolt down cover. Specially fabricated models are also available upon request.



Model	Size	Height	Length	Width	Weight (lbs.)
104121224	12"x12"x24" "	24 ³ / ₄ "	12 3/8"	12 3/8"	30.0
104161624	16"x16"x24" "	24 ³ / ₄ "	17 1/8"	17 1/8"	70.0
104181824	18"x18"x24" "	24 ³ / ₄ "	19 1/8"	19 1/8"	80.0
104202024	20"x20"x24" "	24 ³ / ₄ "	21 1/8"	21 1/8"	95.0
104242424	24"x24"x24" "	24 ³ / ₄ "	25 1/8"	25 1/8"	128.0
104243624	24"x36"x24" "	24 ³ / ₄ "	25 1/8"	36 7/8"	165.0
104303024	30"x30"x24" "	24 ³ / ₄ "	31 1/8"	31 1/8"	148.0
104363624	36"x36"x24" "	24 ³ / ₄ "	37 1/8"	37 1/8"	202.0
104202024W T	20"x20"x24" "	24 ³ / ₄ "	21 1/8"	21 1/8"	95.0
104242424W T	24"x24"x24" "	24 ³ / ₄ "	25 1/8"	25 1/8"	128.0
104303024W T	30"x30"x24" "	24 ³ / ₄ "	31 1/8"	31 1/8"	165.0
104363624W T	36"x36"x24" "	24 ³ / ₄ "	37 1/8"	37 1/8"	202.0
10424X24R	24" x 24"	24 ³ / ₄ "	-	25 1/4"	118.0
10430X24R	30" x 24"	24 ³ / ₄ "	-	31 1/4"	138.0
10436X24R	36" x 24"	24 ³ / ₄ "	-	37 1/4"	192.0
10442X24R	42" x 24"	24 ³ / ₄ "	-	43 1/4"	238.0