

LMK 458



Probe For Marine And Offshore

Ceramic Sensor

accuracy according to IEC 60770:
 standard: 0.25 % FSO
 option: 0.1 % FSO

Nominal pressure

from 0 ... 40 cmH₂O up to 0 ... 200 mH₂O

Output signals

2-wire: 4 ... 20 mA
 others on request

Special characteristics

- ▶ diameter 39.5 mm
- ▶ LR-certificate (Lloyd's Register)
- ▶ GL-certificate (Germanischer Lloyd)
- ▶ DNV-certificate (Det Norske Veritas)
- ▶ CCS-certificate (China Classification Society)
- ▶ high overpressure resistance
- ▶ high long-term stability

Optional versions

- ▶ diaphragm Al₂O₃ 99.9 %
- ▶ different housing materials (stainless steel, CuNiFe)
- ▶ IS-version zone 0
- ▶ screw-in and flange version
- ▶ accessories e.g. assembling and probe flange, mounting clamp

The hydrostatic probe LMK 458 has been developed for measuring level in service and storage tanks and is as a consequence certificated for shipbuilding and offshore applications.

A permissible operating temperature of up to 125°C and the possibility to use the device in intrinsic safe areas enable to measure the pressure of various fluids under extreme conditions. The basis for the LMK 458 is a capacitive ceramic sensor element designed by BD|SENSORS, which offers a high overload resistance and medium compatibility.

Preferred areas of use are



Water

drinking water abstraction
 desalinization plant



Shipbuilding / Offshore


ballast tanks
 monitoring of a ship's position and draught
 level measurement in ballast and storage tanks




Pressure ranges																	
Nominal pressure ¹	[bar]	0.04	0.06	0.1	0.16	0.25	0.4	0.6	1	1.6	2.5	4	6	10	16	20	
Level	[mH ₂ O]	0.4	0.6	1	1.6	2.5	4	6	10	16	25	40	60	100	160	200	
Overpressure	[bar]	2	2	4	4	6	6	8	8	15	25	25	35	35	45	45	
Permissible vacuum	[bar]	-0.2		-0.3		-0.5				-1							
¹ available in gauge and absolute; nominal pressure ranges absolute from 1 bar																	
Output signal / Supply																	
Standard	2-wire: 4 ... 20 mA / V _S = 9 ... 32 V _{DC}						V _{S rated} = 24 V _{DC}										
Option IS-version	2-wire: 4 ... 20 mA / V _S = 14 ... 28 V _{DC}						V _{S rated} = 24 V _{DC}										
Performance																	
Accuracy ²	standard: ≤ ± 0.25 % FSO						option: for P _N ≥ 0.6 bar ³ : ≤ ± 0.1 % FSO										
Permissible load	R _{max} = [(V _S – V _{S min}) / 0.02 A] Ω																
Long term stability	≤ ± 0.1 % FSO / year at reference conditions																
Influence effects	supply: 0.05 % FSO / 10 V						permissible load: 0.05 % FSO / kΩ										
Turn-on time	700 msec																
Mean response time	< 200 msec								mean measuring rate 5/sec								
Max. response time	380 msec																
² accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability)																	
³ Under the influence of disturbance burst according to EN 61000-4-4 (2004) +2 kV accuracy decreased to ≤ ± 0.25 % FSO.																	
Thermal effects / Permissible temperatures																	
Thermal error	≤ ± 0.1 % FSO / 10 K						in compensated range -20 ... 80 °C										
Permissible temperatures	medium / electronics / environment: -25 ... 125 °C						storage: -40 ... 125 °C										
Electrical protection ⁴																	
Short-circuit protection	permanent																
Reverse polarity protection	no damage, but also no function																
Electromagnetic compatibility	emission and immunity according to																
	- EN 61326						- Germanischer Lloyd (GL)						- Det Norske Veritas (DNV)				
⁴ additional external overvoltage protection unit in terminal box KL 1 or KL 2 with atmospheric pressure reference available																	
Mechanical stability																	
Vibration	4 g (according to GL: curve 2 / according to DNV: Class B / basis: DIN EN 60068-2-6)																
Electrical connection																	
Cable outlet	shielded cable with integrated air tube for atmospheric reference (for nominal pressure ranges sealed gauge and absolute, the air tube is plugged)																
Materials																	
Housing	standard: stainless steel 1.4404 (316L) option: CuNi10Fe1Mn (resistant against sea water) others on request																
Seals (media wetted)	standard: FKM options: EPDM, FFKM (min. permissible temperature from -15 °C) others on request																
Diaphragm	standard: ceramics Al ₂ O ₃ 96 % option: ceramics Al ₂ O ₃ 99.9 %																
Cable sheath	TPE -U (flame-resistant, halogen free, increased resistance against oil and gasoline, resistant against salt, sea water, heavy oil)																
Miscellaneous																	
Optionally cable protection	stainless steel pipe for probe in stainless steel: available as compact product (standard: stainless steel pipe with a total length up to 2 m possible; other lengths on request)																
Ingress protection	IP 68																
Current consumption	max. 21 mA																
Weight	min. 650 g (without cable)																
CE-conformity	EMC Directive: 2004/108/EC																
Option Pt 100 temperature element ⁵																	
Temperature range	-25 ... 125°C																
Connection temperature element	3-wire																
Resistance	100 Ω at 0°C																
Temperature coefficient	3850 ppm/K																
Supply I _S	0.3 ... 1.0 mA _{DC}																
Category of the environment																	
Lloyd's Register (LR)	EMV1, EMV2, EMV3, EMV4						number of certificate: 13/20055										
Germanischer Lloyd (GL)	D, EMC 1						number of certificate: 60 481 - 09 HH										
Det Norske Veritas (DNV)	temperature: D						humidity: B				vibration: B						
	electromagnetic compatibility: B						number of certificate: A-12144										
IS-protection																	
Approval DX14A-LMK 458	IBExU 07 ATEX 1180 X						zone 0: II 1G Ex ia IIB T4										
Safety technical maximum values	U _i = 28 V, I _i = 93 mA, P _i = 660 mW, C _i = 105 nF; L _i = 5 µH; the supply connections have an inner capacity of max. 140 nF opposite the enclosure																
Permissible temp.for environment	in zone 0 ⁶ : -20 ... 60°C with p _{atm} 0.8 bar up to 1.1 bar zone 1 and higher: -25 ... 70°C																
Connecting cables (by factory)	cable capacity:						signal line/shield as well as signal line/signal line: 160 pF/m										
	cable inductance:						signal line/shield as well as signal line/signal line: 1 µH/m										
⁵ only for 4...20mA, cable lenght max. 5m																	
⁶ for optional stainless steel pipe the following designation is valid: "II 1 G Ex ia IIC T4" (zone 0)																	

Wiring diagrams

2-wire-system (current)



2-wire-system (current) with Pt 100





Pin configuration


Electrical connection	cable colours (DIN 47100)
Supply V _S +	wh (white)
Supply V _S -	bn (brown)
Option Pt 100 temperature element:	
Supply T+ (with Pt 100)	ye (yellow)
Supply T- (with Pt 100)	gy (grey)
Supply T- (with Pt 100)	pk (pink)
Shield	gn/ye (green / yellow)

Dimensions (in mm)


probe versions



screw-in version




flange version



Probe flange for flange version	
Technical Data	
Suitable for	LMK 382, LMK 382H, LMK 458
Flange material	stainless steel 1.4404 (316L)
Hole pattern	according to DIN 2507
Version	Size (in mm)
DN25 / PN40	D = 115, k = 85, d4 = 68, b = 18, f = 2, n = 4, d2 = 14
DN50 / PN40	D = 165, k = 125, d4 = 102, b = 20, f = 3, n = 4, d2 = 18
DN80 / PN16	D = 200, k = 160, d4 = 138, b = 20, f = 3, n = 8, d2 = 18
Ordering type	
Probe flange DN25 / PN40	ZSF2540
Probe flange DN50 / PN40	ZSF5040
Probe flange DN80 / PN16	ZSF8016

Assembling flange with cable gland	
Technical Data	
Suitable for	all probes
Flange material	stainless steel 1.4404 (316L)
Material of cable gland	standard: brass, nickel plated on request: stainless steel 1.4305 (303); plastic
Seal insert	material: TPE (ingress protection IP 68)
Hole pattern	according to DIN 2507
Version	Size (in mm)
DN25 / PN40	D = 115, k = 85, b = 18, n = 4, d = 14
DN50 / PN40	D = 165, k = 125, b = 20, n = 4, d = 18
DN80 / PN16	D = 200, k = 160, b = 20, n = 8, d = 18
Ordering type	
Assembling Flange DN25 / PN40	ZMF2540
Assembling Flange DN50 / PN40	ZMF5040
Assembling Flange DN80 / PN16	ZMF8016

cable gland M16x1.5 with
seal insert (for cable-Ø 4 ... 11 mm)



Ordering code LMK 458

□	□	□	-	□	□	□	□	-	□	-	□	-	□	-	□	-	□	-	□	□	□	-	□	□	□
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

[illegible]¹ nominal pressure ranges absolute from 1 bar

² mounting accessories are not part of supply and have to be ordered separately

³ min. permissible temperature from -15°C⁴ shielded cable with integrated air tube for atmospheric reference

⁴ stainless steel pipe is not part of the supply